

Product Data Sheet

## **LUBRALL MULTIPURPOSE GREASE**

### **Lubrall AP2/AP3 GREASE PREMIUM**

#### **DESCRIPTION:-**

- These are lithium soap multipurpose greases having high drop point, good thermal and structural stability.
- It has high degree of resistance to oxidation, rusting, corrosion and water washout.

#### **APPLICATION:-**

- These greases also find wide application in both **antifriction and plain bearing of general machinery & farm equipment's**.
- This grease can be used in both industrial and automotive applications. It ensures the lubrication of components, working under very heavy or shock load, like bearings, slide-bearings, axles and joints. It can be used for the lubrication of electromotors or ventilators.
- Recommended for the lubrication of automotive chassis components, wheel bearings, clutch bearings, universal joints and ball joints of steering and suspension systems of passenger cars, trucks, farm tractors and most other types of mobile equipment operating under moderate conditions.
- The recommended operating temperature range is -20°C to 130°C.

**SPECIFICATION:-**

<b><u>SR. NO.</u></b>	<b><u>TEST PARAMETERS</u></b>	<b><u>TEST METHOD</u></b>	<b><u>AP 2 GREASE</u></b>	<b><u>AP3 GREASE</u></b>
1	NLGI Classification		02	03
2	Texture/Appearance		Yellow Color Smooth & Tacky	Yellow Color Smooth & Tacky
3	Soap Type		Lithium	Lithium
4	Drop Point °C	ASTM D 2265	190-205	190-205
5	Base Oil Viscosity @ 40 °C, Cst, min	ASTM D 445	105	105
6	Worked Penetration @ 25 °C 60 X	ASTM D 217	265-290	230-250

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

**"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."**


**LUBRALL INDUSTRIES PVT LTD PLOT NO:**  
 B-73/1/2/3, CHAKAN MIDC,  
 PHASE NO -II, BHAMBOLI, DIST- PUNE-410507  
[www.lubrall.com](http://www.lubrall.com) email- [lubralloil@gmail.com](mailto:lubralloil@gmail.com)