



AUTOMOTIVE | INDUSTRIAL | SPECIALITY LUBRICANTS

Product Data Sheet

Lubrall Black 2 (Heavy-Duty Aluminum Complex Grease)

Product Description:

Lubrall Black 2 is a high-performance grease made for tough environments – perfect for construction, quarry, and mining equipment. It works well in dusty, wet, and hot conditions, and handles heavy loads with ease.

Key Features:

- **Water Resistant** – Does not wash out in rain or washdowns.
- **Heavy Load Protection** – With EP additives to reduce wear.
- **High Temperature Stability** – Works in both hot and cold climates.
- **Rust Protection** – Prevents corrosion and rust on metal parts.
- **Stays in Place** – Tacky and adhesive, doesn't fling off.

Applications:

- Excavators, loaders, bulldozers
- Bearings, pins, bushings
- Off-road & mining machinery
- Wet or outdoor working environments

Typical Properties:

1.	Property	Value
2.	NLGI Grade	2
3.	Thickener Type	Aluminum Complex
4.	Color	Black
5.	Texture	Smooth & Tacky
6.	Dropping Point	260°C
7.	Operating Temp. Range	-10°C to +204°C
8.	Penetration (60 Strokes)	265 – 295
9.	Timken OK Load	45 lbs



AUTOMOTIVE | INDUSTRIAL | SPECIALITY LUBRICANTS

10.	Four Ball Weld Load	400 kg
11.	Water Washout	<5%
12.	Rust Test	Pass

Packaging Options:

- 18 kg Pail
- 180 kg Drum

Storage:

Keep in a cool, dry place. Close container after use. Shelf life is 5 years.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."



LUBRALL INDUSTRIES PVT LTD
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com