

PRODUCT DATA SHEET

LUBRALL CALCIUM MPSP GREASE

DESCRIPTION: -

- These are Golden Yellow Colour Calcium Soap multipurpose grease.
- They possess excellent water resistant, anti-rust & anti corrosive properties.
- This grease acts as protective layer on exposed parts.
- It is also suitable for certain open & semi enclosed gears as well as chain drives of farm equipment.

APPLICATION:-

- They are recommended for general application & plain & anti friction bearing where operating temperatures are moderate **75-80 °C**.
- They can be used for **Water Pumps and Wheel Bearings operating at moderate temperature**.
- This grease is recommended for **general chassis lubrication including suspension & steering system**.

SPECIFICATION:-

<u>SR.NO.</u>	<u>TEST PARAMETERS</u>	<u>TEST METHOD</u>	<u>VALUES</u>
1	Texture/Appearance		Golden Yellow, Smooth & Slightly fibrous
2	Soap		Calcium
3	NLGI Classification		03
4	Drop Point °C	ASTM D 2265	105-115
5	Worked Penetration @ 25 °C after 60 strokes,0.1 mm units	ASTM D 217	230-250
6	Unworked Penetration@25°C,0.1 mm units		225-245

NOTE – WE ALSO HAVE MPSP BASED, NLGI 1/2/0/00/000 BASED CALCIUM GREASE. ALSO AVAILABLE IN RED COLOR.

Packing: - 180 kg drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

 **LUBRALL INDUSTRIES PVT LTD**
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com