

PRODUCT DATA SHEET

LUBRALL MP-2/MP-3 GREASE

DESCRIPTION:-

- These are multipurpose greases having good drop point, good thermal and structural stability.
- It has high degree of resistance to oxidation, rusting, corrosion.
- The grease also provides good resistance to water wash-out.

APPLICATION USE: -

- These greases also find wide application in both **antifriction and plain bearing of general machinery & farm equipment's**.
- Recommended for lubrication of industrial plain/ roller bearings, electric motor bearings, water pump bearings, conveyors, machine tools.
- This grease can be used in both industrial and automotive applications. It ensures the lubrication of components like bearings, slide-bearings, axles and joints. It can be used for the lubrication of electromotors or ventilators.
- Recommended for the lubrication of automotive chassis components, wheel bearings, clutch bearings, universal joints and ball joints of steering and suspension systems of passenger cars, trucks, farm tractors and most other types of mobile equipment.
- **The recommended operating temperature range is -20°C to 120°C.**

SPECIFICATION:-

<u>SR. NO.</u>	<u>TEST PARAMETERS</u>	<u>TEST METHOD</u>	<u>MP-2 GREASE</u>	<u>MP-3 GREASE</u>
1	NLGI Classification		02	03
2	Texture/Appearance		Yellow Color Smooth & Tacky	Yellow Color Smooth & Tacky
3	Soap Type		Lithium Calcium	Lithium Calcium
4	Drop Point °C	ASTM D 2265	180-188	180-188
5	Base Oil Viscosity @ 40 °C, Cst, Min	ASTM D 445	105	105
6	Worked Penetration @ 25 °C 60 X	ASTM D 217	265-290	225-250

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

LUBRALL INDUSTRIES PVT LTD
 PLOT NO: B-73/1/2/3, CHAKAN
 MIDC, PHASE NO -II, BHAMBOLI,
 DIST- PUNE-410507. www.lubral.com
 email- lubralloil@gmail.com

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under.