

PRODUCT DATA SHEET

CUT-BR 35**(Medium High Viscosity Neat cutting oil)**

Lubrall's Cut BR 35 is a medium-high viscosity neat cutting oil, specially formulated to meet the demanding requirements of modern machining operations. This cutting fluid is designed to provide excellent lubrication and cooling properties, ensuring extended tool life and improved surface finish. Cut BR 35 is ideal for use in applications where high temperatures and pressures are present, such as heavy-duty machining of tough materials like stainless steel, titanium, and nickel alloys.

Advantages:

Its high film strength and thermal stability help prevent built-up edge and welding, reducing the risk of tool wear and improving machining efficiency. Additionally, Cut BR 35 offers excellent rust protection, ensuring that machined parts remain in top condition even in harsh environments. Its superior flushing properties help remove chips and debris from the cutting zone, further enhancing machining performance. Overall, Lubrall's Cut BR 35 is a reliable and high-performance cutting oil that can help improve the efficiency and quality of your machining operations

Specification

1	Colour	Light Yellow
2	Density @29	0.82-0.88
3	Viscosity	32-38 Cst
4	Flash Point	>200 ° C
5	Corrosion Test	Pass
6	EP additive	Added
7	Easter	Absent
8	Sulphar	Present

Packing: - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."

LUBRALL INDUSTRIES PVT LTD
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com