

PRODUCT DATA SHEET

LUBRI QUENCH-B 05
(Medium-Fast Quenching oil)

Lubrall's LUBRI QUENCH -B 05 is a medium-fast heat treatment oil specially designed for accelerated quenching applications. It is formulated by blending high-quality mineral oil with fatty materials to provide excellent wetting characteristics. This ensures that the oil can quickly and efficiently absorb heat from the metal being quenched, allowing for rapid cooling and hardening of the material. The use of LUBRI QUENCH -B 05 can result in improved process efficiency and enhanced part performance in heat treatment operations.

APPLICATION :

- Ideally suited for components and materials that demand optimum hardness characteristics through accelerated quenching operations.
- Especially suitable for quenching of high speed tools, ball bearings and other components.

Specification

1	Colour	Yellow Liquid
2	Density @29	0.810-0.830
3	Viscosity @ 40	28-30 Cst
4	Flash Point	>200⁰ C
5	Corrosion Test	Pass
6	Pour Point	< - 6⁰ C
7	Viscosity Index	100

Packing: - 210 Liter drum.

NON-WARRANTY: The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."



LUBRALL INDUSTRIES PVT LTD
PLOT NO: B-73/1/2/3, CHAKAN MIDC,
PHASE NO -II, BHAMBOLI, DIST- PUNE-410507
www.lubrall.com email- lubralloil@gmail.com