

## PRODUCT DATA SHEET

## **HIPOWERHLP-32/46/68/100/150/220**

**(Hydraulic oil HLP Grade Series)**

Lubrall's Hi Power HLP grade hydraulic oil is a high-quality product with a high viscosity index, available in various viscosities to suit different application requirements

**Advantages.**

Some key features and applications of this product include:

**High Viscosity Index:** The high viscosity index of this hydraulic oil ensures consistent performance across a wide range of operating temperatures, providing excellent lubrication and protection.

**Excellent Anti-Wear Properties:** Hi Power HLP grade hydraulic oil is formulated with additives that provide excellent anti-wear properties, protecting hydraulic components from wear and extending equipment life.

**Corrosion and Oxidation Resistance:** This hydraulic oil offers high resistance to corrosion and oxidation, ensuring long-term stability and performance in hydraulic systems. Suitable for Various Applications: Hi Power HLP grade hydraulic oil is suitable for use in a wide range of hydraulic systems, including industrial equipment, mobile machinery, agricultural machinery, and more.

**Available in Various Viscosities:** The product is available in various viscosities, allowing users to select the right grade based on the specific requirements of their equipment and operating conditions. Overall, Lubrall's Hi Power HLP grade hydraulic oil is a reliable choice for hydraulic systems requiring high viscosity index oils, offering excellent performance, protection, and versatility.

**Specification:**

| Product          | API Grade | Sp. Gravity | Viscosity @40° C | VI   | Flash Point °C | Pour Point °C | Copper corrosion |
|------------------|-----------|-------------|------------------|------|----------------|---------------|------------------|
| HI POWER HLP 32  | 32        | 0.830-0.870 | 29-34            | >100 | >200           | -3            | 1A               |
| HI POWER HLP 46  | 46        | 0.830-0.875 | 44-49            | >100 | >200           | -3            | 1A               |
| HI POWER HLP 68  | 68        | 0.840-.880  | 64-72            | >100 | >200           | -3            | 1A               |
| HI POWER HLP 100 | 100       | 0.840-0.885 | 94-105           | >100 | >200           | -3            | 1A               |
| HI POWER HLP 150 | 150       | 0.840-0.885 | 143-160          | >100 | >200           | -3            | 1A               |
| HI POWER HLP 220 | 220       | 0.850-0.885 | 200-235          | >100 | >200           | -3            | 1A               |

**Packing:** - 210 Liter drum.

**NON-WARRANTY:** The information in this bulletin is based on our experience and tests which we believe to be reliable, but offer no guarantee and accept no responsibility for operations not under our direct control.

**"FOR ANY COMPLAINTS CALL on: +91 9763686372 WITH DETAILS OF BATCH NO."**

 LUBRALL INDUSTRIES PVT LTD  
 PLOT NO: B-73/1/2/3, CHAKAN MIDC,  
 PHASE NO -II, BHAMBOLI, DIST- PUNE-410507  
[www.lubrall.com](http://www.lubrall.com) email- [lubralloil@gmail.com](mailto:lubralloil@gmail.com)